

#### Instructions for vehicles with Analog Instrument Cluster

1. On the Climate Control Panel (CCP) press the Warm and Off buttons together. Instrument cluster will light all lights then go blank. This signals entering of diagnostic mode. Press and hold passenger cooler button until "RFA" is displayed then press FAN UP. If "RFA Data" is displayed press FAN DOWN. If "RFA OVERRIDE" is displayed press FAN UP. If " RFA 500 NO OVERRIDE" is displayed press FAN DOWN. If "RFA 501 PROGRAM FOB # 1" is displayed press fan up.
2. Instrument cluster will display a 0 on the right side of the display. Press warmer button on climate control until "99" is displayed.
3. Press Trunk button on the remote being programmed. Next press the Lock button on the transmitter. Hold both buttons until locks cycle. IF remote is not programmed repeat process from step 1.
4. For an additional remote press FAN DOWN button until "RFA 502 PROGRAM FOB # 2" is displayed next press FAN UP and repeat previous step.
5. To exit press Auto or Reset.

#### Instructions for vehicles with Digital Instrument Cluster.

1. On the climate control center press Off and Warm buttons. Instrument Cluster will light all lights than go blank. This signals entering of diagnostic mode. Press Fan up or down until "RFA" is displayed then press FAN UP. Press FAN DOWN until "RFA OVERRIDE" is displayed then press FAN UP. When "NO OVRD RF 500 " is displayed, than press FAN UP button.
2. When " Program Fobl 501" is displayed press warm button "99" will be displayed on the instrument cluster. Now vehicle is in programming mode.
3. Press and hold Trunk button on remote being programmed, While holding Trunk press Lock button and hold for one second. Locks will cycle when programming is complete.
4. To program a second remote press FAN UP button until "Program FOB 2 502" is displayed. Follow previous step to program second remote.
5. Press Recirc or Reset to end programming mode.